



High photosynthesis (H) ± 0.1	The female seat height (H1) ± 0.05	The male seat height (H2) ± 0.05
1.5	1.32	1.25
2.0	1.82	1.25
2.5	2.32	1.25

Electrical
 Voltage: 50 V AC(rms)/DC
 Current: 0.5A AC(rms)/DC
 Contact Resistance: 40 M Ωmax(initial)
 Dielectric Withstanding Voltage: 200 V AC/rms
 Insulation Resistance: 100 MΩ min
 Operating Temp: -40° C ~ +85° C

Ordering Information

SGD-DC-BM-05-***P-H125
 F=Female PITCH NO. of pins The female or Male
 M=Male 05=0.5mm 010~080pin seat height
 125=1.25mm

P 数	尺 寸		
	A	B	C
005	5.50	3.40	2.00
006	6.00	3.90	2.50
007	6.50	4.40	3.00
008	7.00	4.90	3.50
009	7.50	5.40	4.00
010	8.00	5.90	4.50
011	8.50	6.40	5.00
012	9.00	6.90	5.50
013	9.50	7.40	6.00
014	10.00	7.90	6.50
015	10.50	8.40	7.00
016	11.00	8.90	7.50
020	13.00	10.90	9.50
025	15.50	13.40	12.00
030	18.00	15.90	14.50
040	23.00	20.90	19.50



深圳市山谷道电子有限公司
 电话: 0755-27759859 传真: 0755-27759850

RECOMMENDED PCB PATTERN DIM.

TOLERANCE : ±0.05



修订	修改摘要	签名	日期
REV	REVISION DESCRIPTION	SIGNATURE	DATE

一般公差 GENERAL TOLERANCE A ±0.30 .XX ±0.20 MM ±0.10 mm ±0.10	制图 (DRW): Kavin 2024.06.30	品名 (TITLE): 单槽 0.5-H1.5-2.5 公座无柱
审核 (CHKD):	料号 (PART NO.): SGD-DC-BM-05-***P-H125	单位 (UNITS): mm
批准 (APPD):	比例 (SCALE): 1:8	张数 (SHEET): 1 OF 1
		图幅 (SIZE): A4